



MEGA FLEX

High Solids Ultra Compatible Finish

Concentro Altamente Final Ultra Compatible Del Piso



Availability:

Packaging	Item #
4-1 F Gal.:	107249
2-2.5 Gal.:	107245
Pail/ 5 Gal.:	107242
Drum/ 55 Gal.:	107260

Vinyl Tile
Azulejo del vinilo

Linoleum
Linóleo

Terrazzo
Terrazo

Concrete
hormigón

Slate
pizarra

DESCRIPTION

A new generation floor finish formulated with a patented polymer technology that is designed to work with any type of maintenance program and any equipment on all types of floors due to its ultra-compatibility and flexibility. This high-solids finish requires fewer coats and provides superior gloss, excellent durability and superior leveling. New chemistry allows the finish to form good film even in poor drying conditions. Excellent response with any type of UHS equipment - propane, battery, or cord electric. Easy to apply and ideal for weekly burnishing.



FLOOR COATING AND FINISHING
MATERIAL AS TO SLIP
RESISTANCE ONLY 17SU




1048 Stinson Drive, Reading PA 19605
Phone: 1-800-548-4568

www.miscoproducts.com

MEGA FLEX

High Solids Ultra Compatible Finish



Scan for product's
Safety Data Sheet

FEATURES

- High solids
- Easy to apply
- Ultra-compatible
- Flexible maintenance

BENEFITS

- Requires less coats saving labor costs
- Levels excellent and dries fast
- Use on almost any type of floor
- Responds to any floor care program

AREAS OF USE:

- Supermarkets
- Retail stores
- Healthcare facilities
- Hallways
- Office buildings
- Vinyl Tiles
- Linoleum
- Terrazzo
- Slate
- Concrete

SPECIFICATIONS:

Color:
White

Odor:
Fragrance Free

pH:
8.0 – 9.0

Non-Volatile Solids:
25%

Coverage:
1800 – 2200 ft² / gal.

Dry/Recoat Time:
30 minutes min.

Recommended Coats:
4

Maintenance Schedule:
Weekly burnish or spray buff

Slip Resistance:
0.5 min. by ASTM-D2047

Storage/Stability:
1 year

Weight Per Gallon:
8.68lbs./gal.

Freeze/Thaw Stability:
3 cycles

DIRECTIONS

PREPARATION: If stripping is necessary, use a high quality stripper and follow the directions accordingly. Follow with a thorough rinsing and allow floor to dry completely.

If stripping is not necessary; sweep up loose dirt and dust. Clean with a quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow floor to dry completely.

FINISHING: Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Four coats is ideal initially, depending on the condition of the floor and desired gloss.

MAINTENANCE: The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by state and Federal regulations

HAZARD STATEMENTS

May be mildly irritating to eyes and skin.

PRECAUTIONARY STATEMENTS

Do not get in eyes, on skin, or on clothing.

Keep out of reach of children.

Wash thoroughly after handling.

FIRST AID

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

STORAGE

Keep container closed to prevent drying out.

Avoid contact with skin and eyes. Wash hands before eating, drinking, smoking or using toilet facilities.

Store containers away from children. Close container after use.

SPILL/LEAK

Avoid walking in product. Wipe up or otherwise flush to sanitary sewer.

DISPOSAL

Dispose of contents/container in accordance with local, state and federal regulations.

INGREDIENTS

Acrylate Copolymer - (N/A), Diethylene Glycol Ethyl Ether - (111-90-0), 2,5-furandione, polymer with propene - (25722-45-6), Tributoxylethyl Phosphate - (78-51-3), Dibutyl Phthalate - (84-74-2), Water - (7732-18-5).



1048 Stinson Drive, Reading PA 19605

Phone: 1-800-548-4568

www.miscoproducts.com