



## HAND PROTECTION

# Supported Cotton Lined Rubber Gloves

## DESCRIPTION

These gloves are constructed of flexible natural rubber on an interlock liner. That are 12 inches long with a rough wet grip finish. The rubber gives great dexterity and grip. They are also treated with Actifresh® to minimize bacteria that leads to odors.

## INDUSTRY

Construction	Sheet Metal Work
Fishing	Food Processing
Glass Handling	Agricultural Chemicals
Masonry	Farming
Painting	



## FEATURES

- EN 388 Levels: 4131X
- EN 407 Levels: X2XXXX
- EN 374 Levels: AKLMNPST
- Actifresh® treated liner to reduce bacteria which cause smell and can lead to dermatitis
- Curved-finger, contoured palm, excellent fit
- Interlock knit cotton liner helps absorb perspiration
- Launderable

## ITEM 212

## SIZES 8(M)-10(XL)



## SPECIFICATIONS

SHELL		LINER		COLOR	COATING	COATING TYPE	COATING COLOR
Knit Cotton Interlock		Knit Cotton Interlock		Blue	Double Rubber	Full	Blue
FINISH	LENGTH	CUFF	ACTIFRESH TREATED	EN 388 LEVELS		EN 374 LEVELS	EN 407 LEVELS
Rough	12 in	Pinked	Yes	4131X		AKLMNPST	X2XXXX

## PACKAGING

	QUANTITY	8(M)	9(L)	10(XL)
PAIR UPC	1	N/A	N/A	N/A
INNER PACK GTIN	12/PACK	816679014183	816679014190	816679014206
CASE GTIN	6 PK/CASE	10816679014180	10816679014197	10816679014203
CASE WEIGHT (IN POUNDS)		26.4	29.4	30.6

## PERMEATION DATA

EN ISO 374-01: 2016	CHEMICAL	PL
A	Methanol	6
K	Sodium Hydroxide 40%	6
L	Sulfuric Acid 96%	4
M	Nitric Acid 65%	6
N	Acetic Acid 99%	3
P	Hydrogen Peroxide 30%	6
S	Hydrofluoric Acid 40%	5
T	Formaldehyde 37%	6

PERMEATION DATA WAS MEASURED IN TWO WAYS:  
1. FOR SOLVENTS – GAS CHROMATOGRAPHY  
2. FOR ACID AND BASES –  
BY CONDUCTIVITY MEASUREMENTS

\* PL = Performance level

13915 Radium St NW  
Ramsey, MN 55303

763-450-0110  
Sales@GlobalGlove.com

GlobalGlove.com

  
**Global Glove**  
& Safety Manufacturing, Inc.