



AQUATHANE HP

High Performance Hard Surface Seal/Finish

De Alto Rendimiento Del Sello Superficie Dura/Acabado



Availability:

Packaging	Item #
2-2.5 Gal.:	105149
Pail/ 5 Gal.:	105147
Drum/ 55 Gal.:	105152

Flagstone
losa

Concrete
hormigón

Terrazzo
Terrazo

Quarry Tile
Azulejo de la mina

Brick
Ladrillo

DESCRIPTION

A protective acrylic coating, for curing and sealing old non-resilient hard surfaces, such as concrete, terrazzo, brick, unglazed ceramic tile, slate or other stone surfaces. This water based coating should be used for interior applications only. Protects against grease, dirt, chemicals, and stains. Fast drying with no solvent fumes makes this an ideal product for use in closed areas.

Manufacturer's Recommendation: This coating is to be applied without thinning.
VOC Content = 73.2 grams/liter, excluding water




1048 Stinson Drive, Reading PA 19605

Phone: 1-800-548-4568

www.miscoproducts.com



Scan for product's
Safety Data Sheet



AQUATHANE HP

High Performance Hard Surface Seal/Finish

FEATURES

- Metal cross-linked
- Chemical resistant
- No solvent fumes

BENEFITS

- Provides extended wear
- Protects concrete
- Designed for interior use

AREAS OF USE:

- Old concrete surfaces
- Interior concrete
- Concrete
- Terrazzo
- Brick
- Flagstone
- Quarry tile

SPECIFICATIONS:

Color:
White

Odor:
Fragrance Free

pH:
7.5-8.5

Non-Volatile Solids:
20%

Coverage:
1000 – 1500 ft²/gal.

Dry/Recoat Time:
30 minutes min.

Recommended Coats:
2 - 4

Interior/Exterior:
Interior use only

Slip Resistance:
0.5 min. by ASTM-D2047

Storage/Stability:
1 year

Weight Per Gallon:
8.45 lbs./gal.

Freeze/Thaw Stability:
3 cycles

DIRECTIONS

PREPARATION: Remove all grease, oil, and other foreign material by scrubbing with a heavy-duty cleaner and good scrub brushes. For better adhesion on permanent type coatings such as moisture-cured urethanes or epoxies, it is recommended that the surface be abraded with a 100-mesh screen disk. Smooth dense concrete surfaces should be acid conditioned before application. Rinse floor thoroughly with clear water and allow to dry.

APPLICATION: Spread a liberal coat evenly across the floor using a mop, squeegee, roller, lamb's wool applicator or other appropriate applicator. If higher gloss is desired apply a second coat after allowing first coat to dry for at least 45 minutes. Surface temperature should be above 50°F. Allow final coat to dry at least 12 hours before allowing heavy traffic onto floor.

HAZARD STATEMENTS

May be mildly irritating to eyes and skin.

PRECAUTIONARY STATEMENTS

Do not get in eyes, on skin, or on clothing.
Keep out of reach of children.

Wash thoroughly after handling.

FIRST AID

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

STORAGE

Keep container closed to prevent drying out.
Avoid contact with skin and eyes. Wash hands before eating, drinking, smoking or using toilet facilities.

Close container after use.

SPILL/LEAK

Avoid walking in product. Wipe up or otherwise flush to sanitary sewer.

DISPOSAL

Dispose of contents/container in accordance with local, state and federal regulations.

INGREDIENTS

Acrylate Copolymer - (N/A), Diethylene Glycol Ethyl Ether - (111-90-0),
Tributoxyethyl Phosphate - (78-51-3), Dibutyl Phthalate - (84-74-2), Oxidized
Polyethylene - (68441-17-8), Water - (7732-18-5)



1048 Stinson Drive, Reading PA 19605
Phone: 1-800-548-4568

www.miscoproducts.com