



CLASSIC 250

High Solids Floor Finish

Sólidos Altos Final Del Piso



Availability:

Packaging	Item #
4-1 F Gal.:	105427
2-2.5 Gal.:	105432
Pail/ 5 Gal.:	105421
Drum/ 55 Gal.:	105435

Vinyl Tile
Azulejo del vinilo

Linoleum
Linóleo

Terrazzo
Terrazo

Concrete
hormigón

Slate
pizarra

DESCRIPTION

A premium quality, high solids, metal cross-linked acrylic floor finish designed to give exceptional initial gloss with minimum amount of coats. Dries to a hard durable finish that withstands daily high traffic yet responds well to low or high speed spray-buffing. Designed for low or high maintenance floor care programs.



FLOOR COATING AND FINISHING
MATERIAL AS TO SLIP
RESISTANCE ONLY 17SU



1048 Stinson Drive, Reading PA 19605
Phone: 1-800-548-4568

www.miscoproducts.com

CLASSIC 250

High Solids Floor Finish



Scan for product's
Safety Data Sheet

FEATURES

- Metal Cross-linked
- High Solids
- Flexible maintenance
- "Wet look" gloss

BENEFITS

- Provides extended wear
- Requires less coats
- Responds to any floor care program
- Floors look great

AREAS OF USE:

- Classrooms
- Healthcare facilities
- Office buildings
- Hallways
- Entrances
- Hospitals
- Vinyl Tiles
- Linoleum
- Terrazzo
- Slate
- Concrete

DIRECTIONS

PREPARATION: If stripping is necessary, use a high quality stripper and follow the directions accordingly. Follow with a thorough rinsing and allow floor to dry completely.

If stripping is not necessary; sweep up loose dirt and dust. Clean with a quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow floor to dry completely.

FINISHING: Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Four coats is ideal initially, depending on the condition of the floor and desired gloss.

MAINTENANCE: The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.

SPECIFICATIONS:

Color:
White

Odor:
Fragrance Free

pH:
8.0 – 9.0

Non-Volatile Solids:
25%

Coverage:
1800 – 2200 ft² / gal.

Recommended Coats:
4

Dry/Recoat Time:
30 minutes min.

Maintenance Schedule:
Weekly or monthly burnish or spray buff

Slip Resistance:
0.5 min. by ASTM-D2047

Storage/Stability:
1 year

Weight Per Gallon:
8.65lbs./gal.

Freeze/Thaw Stability:
3 cycles

HAZARD STATEMENTS

May be mildly irritating to eyes and skin.

PRECAUTIONARY STATEMENTS

Do not get in eyes, on skin, or on clothing.

Keep out of reach of children.

Wash thoroughly after handling.

FIRST AID

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

STORAGE

Keep container closed to prevent drying out.

Avoid contact with skin and eyes. Wash hands before eating, drinking, smoking or using toilet facilities.

Close container after use.

SPILL/LEAK

Avoid walking in product. Wipe up or otherwise flush to sanitary sewer.

DISPOSAL

Dispose of contents/container in accordance with local, state and federal regulations.

INGREDIENTS

Acrylate Copolymer - (N/A), Oxidized Polyethylene - (68441-17-8), Dipropylene glycol monomethyl ether - (34590-94-8), Diethylene Glycol Ethyl Ether - (111-90-0), Tributoxyethyl Phosphate - (78-51-3), Water - (7732-18-5)



1048 Stinson Drive, Reading PA 19605
Phone: 1-800-548-4568

www.miscoproducts.com