





# Dominator Extra Heavy Duty Strip

## PRODUCT SPECIFICATIONS

# 1.0 Description

The Dominator is an extra aggressive floor maintenance stripping pad constructed of heavy denier polyester fibers in an open texture nonwoven fabrication. Abrasive particles are dispersed throughout and adhered to the nonwoven construction with a sturdy adhesive.

# 2.0 Properties

Property	Value
Thickness	0.87 in 22 mm
Weight	55 osy 1865 gsm
Fiber Type	Recycled Polyester
Binder System	Cross-linkable water based
Binder Application	Spray/Dip
Abrasive Application	Spray/Dip
Abrasive	Yes
Color	Burgundy
Pack	5 per case



Full Cycle® Products are certified by Green Seal® for Environmental Innovation based on faster biodegradation in landfill conditions and 100% recycled content/natural fiber. GreenSeal.org/6520

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact Americo with any questions or concerns.

Americo Manufacturing Company, Inc. 1-800-241-9902

www.americomfg.com

★ 2022
Rev. 4/25/22
Dominator Extra Heavy Duty Strip Product Specifications

#### 3.0 Use

Use with water based floor stripping solution to remove worn and soiled floor finishes or sealers. May also used to clean heavily soiled hard surface floors, such as concrete, when used with proper cleaning solutions. For use on standard electric floor machines or automatic scrubbers. Ideal for use on machines speeds up to 350 rpm.

## 4.0 Construction

The Dominator Extra Heavy Duty Stripping Pad is constructed of polyester fibers along with synthetic adhesives that will not be notably affected by water or cleaners used in standard floor maintenance. The abrasives used in this product are synthetic. This pad has been designed for use on both sides.

### 5.0 Labeling

Labeling is to clearly identify product, size, and quantity. Americo brand or private label is available for this product.

### **6.0 Environmental Initiatives**

- a. Polyester fiber used in our pads come from 100% post consumer and industrial recycled waste product.
- b. Full Cycle®, formulated to biodegrade\* in a fraction of the time that it takes conventional floor pads once discarded into an active landfill.
- c. Water Based Latex Resins are used in the manufacturing process. No phenolformaldehyde resins are used in our binding process.
- Shipping cartons contain at least 45% recycled material.
- e. Plant is operating under EPA approved Clean Air Permit.
- \* For complete details or to view ASTM D5511 test results visit www.AmericoFullCycle.com

#### 7.0 Directions for Use

Dust mop or sweep floors prior to stripping.
Use pad until soil and finish are removed from floor. Pick up stripping or cleaning solution with a mop, wet vacuum or automatic scrubber.
Rinse floor and let dry prior to re-coating or opening to traffic.

#### 8.0 Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

#### 9.0 Sizes

Disc Size (Diameter)	Center Hole
(O.D. ± 0.06 inch)	
12 inch	3.25 inch
13 inch	3.25 inch
14 inch	3.25 inch
15 inch	3.25 inch
16 inch	3.25 inch
17 inch	3.25 inch
18 inch	3.25 inch
19 inch	3.25 inch
20 inch	
21 inch	3.25 inch

#### Rectangular Size

12 inch x 18 inch 14 inch x 20 inch 14 inch x 24 inch 14 inch x 28 inch 14 inch x 32 inch

Additional sizes available.

Check for availability on additional center hole dimensions.

