



FIRST STEP Acrylic Floor Sealer

Sellador Acrílico



Availability:

Packaging	Item #
4-1 F Gal.:	106404
2-2.5 Gal.:	106410
Pail/ 5 Gal.:	106397
Drum/ 55 Gal.:	106414

Vinyl Tile
Azulejo del vinilo

Linoleum
Linóleo

Terrazzo
Terrazo

Concrete
hormigón

Slate
pizarra

DESCRIPTION

An acrylic floor sealer formulated to provide a hard, durable undercoat for use prior to the application of any floor finish. Never yellows and will continue to protect your floor after all floor finish has worn off. Provides chemical and stain resistance and is for use on any type of hard surface.




1048 Stinson Drive, Reading PA 19605
Phone: 1-800-548-4568

www.miscoproducts.com



Scan for product's
Safety Data Sheet



FIRST STEP

Acrylic Floor Sealer

FEATURES

- Acrylic based sealer
- Compatible
- Versatile
- Protects flooring

BENEFITS

- Easy to apply
- Use prior to any acrylic floor finish
- Use on any type of hard surface
- Resists chemicals and stains

AREAS OF USE:

- Classrooms
- Healthcare facilities
- Office buildings
- Hallways
- Entrances
- Hospitals
- Vinyl Tiles
- Linoleum
- Terrazzo
- Slate
- Concrete

DIRECTIONS

PREPARATION: If stripping is necessary, use a high quality stripper and follow the directions accordingly. Follow with a thorough rinsing and allow floor to dry completely.

If stripping is not necessary; sweep up loose dirt and dust. Clean with a quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow floor to dry completely.

SEALING: Spread a liberal coat of sealer evenly across the floor with a clean mop or applicator. For porous, damaged, or well-worn floors, apply 2 coats of sealer prior to the floor finish application. On new floor or floors in good condition, one coat of sealer should suffice. Allow a dry time of at least 30 minutes before applying another coat of sealer or floor finish.

SPECIFICATIONS:

Color:

White

Odor:

Fragrance Free

pH:

8.0 – 9.0

Non-Volatile Solids:

18%

Coverage:

1800 – 2200 ft² / gal.

Recommended Coats:

1 - 2

Dry/Recoat Time:

30 minutes min.

Maintenance Schedule:

N/A

Slip Resistance:

0.5 min. by ASTM-D2047

Storage/Stability:

1 year

Weight Per Gallon:

8.58lbs./gal.

Freeze/Thaw Stability:

3 cycles

HAZARD STATEMENTS

May be mildly irritating to eyes and skin.

PRECAUTIONARY STATEMENTS

Do not get in eyes, on skin, or on clothing.

Keep out of reach of children.

Wash thoroughly after handling.

FIRST AID

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

STORAGE

Keep container closed to prevent drying out.

Avoid contact with skin and eyes. Wash hands before eating, drinking, smoking or using toilet facilities.

Close container after use.

SPILL/LEAK

Avoid walking in product. Wipe up or otherwise flush to sanitary sewer.

DISPOSAL

Dispose of contents/container in accordance with local, state and federal regulations.

INGREDIENTS

Acrylate Copolymer - (N/A), Oxidized Polyethylene - (68441-17-8), Dipropylene glycol monomethyl ether - (34590-94-8), Diethylene Glycol Ethyl Ether - (111-90-0), Tributoxyethyl Phosphate - (78-51-3), Water - (7732-18-5)



1048 Stinson Drive, Reading PA 19605

Phone: 1-800-548-4568

www.miscoproducts.com