

# **REBOUND** High Speed Buffing Creme



Item #

107931

Packaging

12-1 Pt.:

Nata que pulimenta de alta velocidad



## DESCRIPTION

The ideal companion product for use with any high speed maintenance program, this cleaning compound is designed to protect and beautify any resilient tile, sealed wood, ceramic, terrazzo, quarry tile, or other hard surface flooring while reducing time and labor. This high speed burnishing crème will restore floors to the ultimate "wet look" gloss.



# **REBOUND** High Speed Buffing Creme





Scan for product's Safety Data Sheet

#### **FEATURES**

#### BENEFITS

- Restores to an ultra-high gloss
- Designed for high speed maintenance
- 3 4 inch strip of crème covers 800 – 1000 sq. ft.

# Keeps floors looking great

- Will not powder or streak
- Low end use cost

#### **AREAS OF USE:**

- Classrooms
- Healthcare facilities
- Office buildings
- Hallways
- Entrances
- Hospitals

#### DIRECTIONS

Sweep or dust mop the floor to remove all tar, gum, and excess soil that may scratch the finish during the buffing operation. Place a burnishing pad under a 1000 RPM or higher floor machine. Apply a 3-4 inch strip of cream in front of the machine and spread with the pad over an 800 - 1000 square foot area. Once the entire floor is done, sweep or dust the floor again.

HAZARD STATEMENTS May be milidly irritating to eyes and skin. PRECAUTIONARY STATEMENTS Do not get in eyes, on skin, or on clothing. Keep out of reach of children. Wash thoroughly after handling. FIRST AID IF IN EYES: Rinse cautiously with water for several minutes. Bemove contact lenges if present and easy to do Continue

Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **STORAGE** Keep container closed to prevent drying out.

Avoid contact with skin and eyes. Wash hands before eating,

drinking, smoking or using toilet facilities. Close container after use. SPILL/LEAK Avoid walking in product. Wipe up or otherwise flush to sanitary sewer. DISPOSAL

Dispose of contents/container in accordance with local, state and federal regulations. INGREDIENTS

2-Propenoic acid, polymer with ethene - (9010-77-9), Nonylphenol Ethoxylate - (9016-45-9), d-Limonene - (5989-27-5), Propylene Glycol - (57-55-6), Water - (7732-18-5)

### SPECIFICATIONS:

**Color:** White

Odor: Citrus

**pH:** 7.0 - 8.0

Non-Volatile Solids: < 5%

Viscosity: Viscous gel

Foam: Low

**Recommended Dilution:** RTU

Slip Resistance: Will not increase slip resistance

Flashpoint: None

Storage/Stability: 2 years

Weight Per Gallon: 8.55 lbs./gal.

Freeze/Thaw Stability: Keep from freezing



facilities • Linoleum ings • Terrazzo • Quarry Tile

• Vinyl Tiles