

TOPAZ Anti-Slip Gloss Restorer

Restaurador Anti-Slip Del Lustre



Availability:

 Packaging
 Item #

 4-1 F Gal.:
 108842

 2-2.5 Gal.:
 108846

 Pail / 5 Gal.:
 108836

 Drum / 55 Gal.:
 103687

Vinyl Tile Azulejo del vinilo





Quarry Tile Azulejo de la mina Concrete Hormigón

DESCRIPTION

An ideal companion product for use with any high speed maintenance program. Regular use of this product keeps floors looking great day after day. Special proprietary ingredients bond to the surface of the floor to create an anti-slip surface, making it ideally suited for nursing homes, supermarkets, hospitals, schools and other public areas. This product effectively cleans the floor and restores floor finish. Highly concentrated for economical use dilutions, it can be mopped on or used through an automatic scrubber. Once the product dries to a haze, use a high speed burnisher to "pop" the gloss to a brilliant shine.





Topaz Anti-Slip Gloss Restorer





Scan for product's Safety Data Sheet

FEATURES

- One step cleaner/maintainer
- Repairs scuffs and improves gloss
- Highly concentrated
- Improves traction

BENEFITS

- Time and labor cost savings
- Keeps floors looking great
- Low end use cost
- Less exposure to slip and falls

AREAS OF USE:

- Classrooms
- Vinyl Tiles
- Healthcare facilities
- Linoleum
- Office buildings
- Terrazzo
- Hallways
- Quarry Tile
- Entrances
- Concrete
- Hospitals
- Contre

DESCRIPTION

An ideal companion product for use with any high speed maintenance program. Regular use of this product keeps floors looking great day after day. Special proprietary ingredients bond to the surface of the floor to create an anti-slip surface, making it ideally suited for nursing homes, supermarkets, hospitals, schools and other public areas. This product effectively cleans the floor and restores floor finish. Highly concentrated for economical use dilutions, it can be mopped on or used through an automatic scrubber. Once the product dries to a haze, use a high speed burnisher to "pop" the gloss to a brilliant shine.

DIRECTIONS:

Cleaning / Maintaining:

Dust mop all flooring and remove gum and adhesives. Dilute 1 part restorer to 16 parts cool water in the solution tank of the auto-scrubber or mop bucket. Auto-scrub or mop on all flooring using overlapping passes. If auto-scrubbing, dispense, agitate, and pick up the solution. Pick up any puddles with a clean damp mop. Allow to dry thoroughly. Burnish all flooring to clean and restore floor finish.

For Floor Restoring:

Dust mop all flooring and remove any gum or adhesives. Damp mop or auto-scrub floor with a neutral pH floor cleaner following label directions. Dilute 1 part restorer to 4 parts cool water in a mop bucket or auto-scrubber. Apply a thin, even coat on the surface. Do not pickup solution. Allow to dry thoroughly. Burnish all flooring to restore the floor to the ultimate "wet look" shine with a burnishing pad.

Note: Don't allow restorer solution to remain in the auto-scrubber tank. Drain and rinse.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by current State and Federal regulations.

WARNING

HAZARD STATEMENTS Causes eve irritation.

Causes mild skin irritation.

May be harmful if swallowed.

PRÉCAUTIONARY STATEMENTS

Do not get in eyes, on skin, or on clothing.

Keep out of reach of children.

Wear protective gloves/protective clothing/eye protection/face protection. FIRST AID

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel

STORAGE

Store in area inaccessible to children.

Wear eye protection, rubber gloves when handling concentrate

Close container after use

SPILL/LEAK

Avoid walking in product. Wipe up or otherwise flush to sanitary sewer.

DISPOSAL

Dispose of contents/container in accordance with local, state and federal regulations.

INGREDIENTS

Acrylate Copolymer - (N/A), 2-Propenoic acid, polymer with ethene - (9010-77-9), Nonylphenol Ethoxylate - (9016-45-9), Propylene Glycol n-butyl Ether - (5131-66-8), Oxidized Polyethylene - (68441-17-8), Dye - (N/A), Fragrance - (N/A), Water - (7732-18-5)

SPECIFICATIONS:

Color:

Light Orange

Odor:

Fresh

pH:

8.0 - 9.0

Non-Volatile Solids:

8 - 10%

Viscosity:

Water thin

Foam:

Low

Recommended Dilution:

1.16

Slip Resistance:

Increases with regular use

Flash Point:

None

Storage/Stability:

2 years

Weight Per Gallon:

8.36 lbs./gal.

Freeze/Thaw Stability:

Keep from freezing

